











technics	<div><div>In case of precast concrete panels, gear inclusive.</div><div></div></div> <div><div>In case of finished concrete ceiling, gear exclusive.</div><div></div></div>	<table><tr><th>Name</th><th>Reference</th><th>Lamptype</th><th>Ø A</th><th>B</th><th>C</th><th>D</th><th>Ø E</th></tr><tr><td rowspan="7">Concrete plasterkit aplis 80</td><td rowspan="7">KR737702</td><td>QR-CBC51</td><td>152</td><td>320</td><td>320</td><td>200</td><td>170</td></tr><tr><td>LED dir (Kr93773x)</td><td>152</td><td>300</td><td>300</td><td>157</td><td>250</td></tr><tr><td>LED dir (Kr93793x), HE(Kr937X2X)</td><td>152</td><td>344</td><td>344</td><td>120</td><td>380</td></tr><tr><td>Fixed, WW (Kr93703x, Kr93733x)</td><td>152</td><td>260</td><td>260</td><td>100</td><td>250</td></tr><tr><td>Audio</td><td>152</td><td>200</td><td>200</td><td>130</td><td>152</td></tr><tr><td>Diapason 40/80/120 base</td><td>152</td><td>260</td><td>260</td><td>70*</td><td>110</td></tr><tr><td>ATO 80 single and double</td><td>152</td><td>300</td><td>300</td><td>157</td><td>250</td></tr><tr><td rowspan="8">Concrete plasterkit aplis 165</td><td rowspan="8">KR737712</td><td>QT12-ax</td><td>287</td><td>300</td><td>300</td><td>200</td><td>287</td></tr><tr><td>QR-LP111/LED-LP111</td><td>287</td><td>300</td><td>300</td><td>230</td><td>287</td></tr><tr><td>HIT-TC</td><td>287</td><td>300</td><td>300</td><td>230</td><td>287</td></tr><tr><td>HIR-CE111</td><td>287</td><td>300</td><td>300</td><td>230</td><td>287</td></tr><tr><td>QT12-ax WW</td><td>287</td><td>300</td><td>300</td><td>175</td><td>287</td></tr><tr><td>HIT-TC WW</td><td>287</td><td>300</td><td>300</td><td>205</td><td>287</td></tr><tr><td>LED wallwasher</td><td>287</td><td>300</td><td>300</td><td>200</td><td>287</td></tr><tr><td>LED</td><td>287</td><td>300</td><td>300</td><td>200</td><td>287</td></tr><tr><td rowspan="2">Concrete plasterkit aplis 40</td><td rowspan="2">KR737602</td><td>LED dir, fixed, WW</td><td>110</td><td>110</td><td>110</td><td>80</td><td>110</td></tr></table>	Name	Reference	Lamptype	Ø A	B	C	D	Ø E	Concrete plasterkit aplis 80	KR737702	QR-CBC51	152	320	320	200	170	LED dir (Kr93773x)	152	300	300	157	250	LED dir (Kr93793x), HE(Kr937X2X)	152	344	344	120	380	Fixed, WW (Kr93703x, Kr93733x)	152	260	260	100	250	Audio	152	200	200	130	152	Diapason 40/80/120 base	152	260	260	70*	110	ATO 80 single and double	152	300	300	157	250	Concrete plasterkit aplis 165	KR737712	QT12-ax	287	300	300	200	287	QR-LP111/LED-LP111	287	300	300	230	287	HIT-TC	287	300	300	230	287	HIR-CE111	287	300	300	230	287	QT12-ax WW	287	300	300	175	287	HIT-TC WW	287	300	300	205	287	LED wallwasher	287	300	300	200	287	LED	287	300	300	200	287	Concrete plasterkit aplis 40	KR737602	LED dir, fixed, WW	110	110	110	80	110
Name	Reference	Lamptype	Ø A	B	C	D	Ø E																																																																																																									
Concrete plasterkit aplis 80	KR737702	QR-CBC51	152	320	320	200	170																																																																																																									
		LED dir (Kr93773x)	152	300	300	157	250																																																																																																									
		LED dir (Kr93793x), HE(Kr937X2X)	152	344	344	120	380																																																																																																									
		Fixed, WW (Kr93703x, Kr93733x)	152	260	260	100	250																																																																																																									
		Audio	152	200	200	130	152																																																																																																									
		Diapason 40/80/120 base	152	260	260	70*	110																																																																																																									
		ATO 80 single and double	152	300	300	157	250																																																																																																									
Concrete plasterkit aplis 165	KR737712	QT12-ax	287	300	300	200	287																																																																																																									
		QR-LP111/LED-LP111	287	300	300	230	287																																																																																																									
		HIT-TC	287	300	300	230	287																																																																																																									
		HIR-CE111	287	300	300	230	287																																																																																																									
		QT12-ax WW	287	300	300	175	287																																																																																																									
		HIT-TC WW	287	300	300	205	287																																																																																																									
		LED wallwasher	287	300	300	200	287																																																																																																									
		LED	287	300	300	200	287																																																																																																									
Concrete plasterkit aplis 40	KR737602	LED dir, fixed, WW	110	110	110	80	110																																																																																																									
		cut out	<p>** Mind that the driver dimensions WxH cannot exceed 67x29,5mm! the length of the driver determines D as it has to be pushed perpendicular through the plasterkit. Depth = length of the driver + 30mm</p>																																																																																																													
dimensions	<div><div></div><div>Aplis 80</div></div> <div><div></div><div>Aplis 165</div></div> <div><div></div><div>Aplis 40</div></div>																																																																																																															
installation	<div><div></div><div>Reinforce perfo plate with gypsum plate or wooden plate to avoid bending.</div></div> <div><div></div><div>Fix the plasterkit with screws.</div></div> <div><div></div><div>Fill around perimeter of plasterkit using suitable filler and plaster to hide screws and plasterkit.</div></div>																																																																																																															
installation	<div><div></div><div>Min 85</div><div>Minimum filler distance, spread out until zero.</div></div> <div><div></div><div>For installing aplis 80 and 165, see the corresponding installation manual.</div></div>																																																																																																															
kreon nv	Industrieweg Noord 1152 3660 Opglabbeek Belgium	Tel + 32 89 81 97 80 Fax + 32 89 81 97 90	www.kreon.com mailbox@kreon.be	revision date: 24/11/2020 KR8370001846	Sheet 1/1																																																																																																											