



# kreon installation manual

## technics & dimensions


Holan 40 pendant



Oran



Oran kap



name	reference	current	Power	ØD/□DxH	L
Holan 40 pendant	KR96200x-xxxx-xxx-xx	700mA	8,4W	45x210	3000
Holan 40 pendant gear incl.	KR96290x-xxxx-xxx-xx	240 V	6,7W	45x210	3000
Oran glass S	KR99112x-xxxx-S-x	700mA	6,7W	70x210	up to 6000
Oran glass L	KR99112x-xxxx-L-x	700mA	6,7W	70x280	up to 6000
Oran Albast	KR99112x-xxxx-A-x	700mA	6,7W	80x210	up to 6000
Oran kap glass S	KR99114x-xxxx-S-x-xx	700mA	6,7W	280x210	up to 6000
Oran kap glass L	KR99114x-xxxx-L-x-xx	700mA	6,7W	280x280	up to 6000
Oran kap Albast	KR99114x-xxxx-A-x-xx	700mA	6,7W	280x210	up to 6000

\* In case of a fixture with albast, mind that the fixture is not placed in direct sunlight.  
The albast will lose its translucent property when material reaches temperatures above 50°C.

## Remarks

For installation of the pendants consult the installation manual of the suspension accessory.

Recessed suspension kit	KR791100
Surface mounted installation box white	KR791001
Surface mounted installation box black	KR791002
Surface mounted gearbox (for 1 module) white	KR791004
Surface mounted gearbox (for 1 module) black	KR791005
Surface mounted gearbox (up to 3 modules) white	KR791006
Surface mounted gearbox (up to 3 modules) black	KR791007

In case of gear exclusive in combination with the surface mounted installation box, the gear cannot be installed above the pendant on the hollow ceiling.  
Driver should be placed at a distance where it still can be reached in case of a problem.

## pictures

