

## IMPORTANT SAFETY INSTRUCTIONS - SAVE THESE INSTRUCTIONS

Installation instructions for KREON - PROLOGE 80 FLUO surface mounted

**! WARNING:** READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE STARTING INSTALLATION. SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE

**! RISK OF FIRE! - RISK OF SHOCK!**  
- INSTRUCTIONS PERTAINING TO A RISK OF FIRE OR INJURY TO PERSONS  
THIS LUMINAIRE MUST BE INSTALLED TO CONFIRM WITH NEC AND ALL LOCAL ELECTRICAL & BUILDING CODES & PRACTICES. TO ASSURE

FULL COMPLIANCE WITH LOCAL CODES AND REGULATIONS, CONSULT WITH YOUR LOCAL ELECTRICAL INSPECTOR BEFORE INSTALLATION.  
- DISCONNECT POWERSUPPLY BEFORE INSTALLING OR SERVICING  
- ENSURE THE LUMINAIRE IS GROUNDED

- LUMINAIRE IS SURFACE MOUNTED ONLY  
- SUITABLE FOR INDOOR DRY LOCATIONS ONLY

WARNING - to reduce the risk of FIRE OR INJURY:  
- turn off power and allow to cool before replacing lamp

### 1 notifications

- lamp gets HOT quickly! contact only switch/plug when turning on  
- do not touch hot lens, guard, reflector or enclosure  
- keep lamp away from materials that may burn  
- do not operate the luminaire with a missing or damaged shield, if required

The luminaire can only be used with Kreon accessories.

This installation manual might not cover all details or variations. When additional information is required, please contact your local representative, or one of the Kreon offices.

Notice de montage pour KREON - PROLOGE 80

**! ATTENTION:** LIRE ET COMPRENDRE TOUTES LES INSTRUCTIONS AVANT L'INSTALLATION. CONSERVER CES INSTRUCTIONS POUR DE FUTURES REFERENCES

**! RISQUE D'INCENDIE! RISQUE DE CHOC!**

- INSTRUCTIONS RELATIVES À UN RISQUE D'INCENDIE OU DE BLESSURE  
- CE PRODUIT DOIT ETRE INSTALLE SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAIT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHERENTS  
- CONSULTER UN ELECTRICIEN QUALIFIE POUR VOUS ASSURER QUE LES CONDUCTEURS DE LA DERIVATION SONT ADEQUATS

- COUPER L'ALIMENTATION AVANT L'ENTRETIEN  
- ASSURER QUE LE LUMINAIRE EST MIS A LA TERRE  
- MONTER LE LUMINAIRE EN SURFACE SEULEMENT  
- POUR EMBLACEMENT SECS SEULEMENT


ALERTE - pour réduire le risque D'INCENDIE OU DE BLESSURE:  
- coupez l'alimentation électrique et laissez refroidir avant de remplacer l'ampoule  
- la lampe chauffe rapidement!  
- ne touchez pas l'objectif à chaud, la garde, le réflecteur ou une enceinte  
- gardez le luminaire loin de matériaux qui peut brûler  
- luminaires équipés avec un verre de sécurité doivent operé d'un verre de

sécurité complet et en place

Le luminaire ne peut être utilisé qu' avec des accessoires de Kreon

Cette notice de montage ne couvre pas tous les détails ou les variations. Pour des informations supplémentaires veuillez contacter votre représentant local ou un des bureaux Kreon.

Prologe 80 fluo




Prologe 80 fluo


Name	Reference	L x W x H
Prologe 80 Fluo	ku96751_ / ku96895_	35 1/2" x 3" x 6 1/8"
Prologe 80 Fluo dimmable	ku(x)96876_ / ku(x)96896_	47 1/4" x 3" x 6 1/8"

### 2 dimensions


## technics




install octagonal junction-box size 4  
aligned with the wall



screw the supplied plasterkit on the  
installed junction-box




plaster the edges of the plasterkit  
do not plaster the centerhole nor  
the slipholes with the nuts




drill 2 holes according to the table  
and insert plugs


## 3 installation



pull cables through centerhole  
and fix housing to ceiling




1. in case of no dimming:  
connect power supply  
L = switched live (black)  
N = neutral (white)




2. in case of dimming:  
connect power supply  
L = switched live (black)  
N = neutral (white)  
D1 = dimsignal - (grey)  
D2 = dimsignal + (violet)

Name	Reference	X
Prologe 80 Fluo	ku96751_ / ku96895_	332/5"
Prologe 80 Fluo dimmable	ku(x)96876_ / ku(x)96896_	452/5"


## 4 connection




fix the housing



insert lamp and fix it with quarterturn




click!



insert louvre

## 5 installation



## 6 lamp placement

kreon nv

Industrieweg Noord 1152  
B-3660 Opglabbeek  
Belgium

Tel + 32 89 81 97 80  
Fax + 32 89 81 97 90

www.kreon.com  
mailbox@kreon.be

Rev. date: 08/2/2010  
KU8657601658