

kreon

technical datasheet

product family

up 80

KR95233x-90xx-DF	up il 80 square diffuser
KR95233x-90xx-WW	up il 80 square wallwasher
KR95233x-90xx-XX	up il 80 square spot or flood
KR95213x-90xx-DF	up 80 square diffuser
KR95213x-90xx-DF-XC	up 80 XC square diffuser
KR95213x-90xx-WW	up 80 square wallwasher diffuser
KR95213x-90xx-WW-XC	up 80 XC square wallwasher diffuser
KR95213x-90xx-XX-XC	up 80 square spot or flood
KR95213x-90xx-XX-XC	up 80 XC square spot or flood
KR95283x-90xx-DF	up il 80 circular diffuser
KR95283x-90xx-WW	up il 80 circular wallwasher
KR95283x-90xx-XX	up il 80 circular spot or flood
KR95263x-90xx-DF	up 80 circular diffuser
KR95263x-90xx-DF-XC	up 80 XC circular diffuser
KR95263x-90xx-WW	up 80 circular wallwasher diffuser
KR95263x-90xx-WW-XC	up 80 XC circular wallwasher diffuser
KR95263x-90xx-XX-XC	up 80 circular spot or flood
KR95263x-90xx-XX-XC	up 80 XC circular spot or flood

general

IP-rate

compliance

material & surface treatment

glass

toppart

bottompart

finishing frame

glass on toppart fixation

sealant

production method

toppart

bottompart

finishing frame

test results

static load finishing frame

static load glass

67

EN60598-1, EN60598-2-13

:

toughened soda lime safety glass

black or white screen print (ceramic, scratch resistant colored)

IK10-grade

PBT 30% GF, V0 classification

aluminum, hard anodizing 30 μm

stainless steel, type 316

natural: sandblasted

black: sandblasted and PVD coated

Nitto double sided tape

sikaflex 256

plastic injection molding

machined

sheetmetal, bending & welding

square: 10kN, circular: 15kN

links to test reports