









technics	<p>In case of precast concrete panels, gear inclusive.</p>  <p>In case of finished concrete ceiling, gear exclusive.</p> 	<table><thead><tr><th>Name</th><th>Reference</th><th>Lamptype</th><th>Ø A</th><th>E</th><th>F</th><th>G</th><th>Ø B</th><th>D</th></tr></thead><tbody><tr><td>Concrete plasterkit aplis IL 80 (shadow gap)</td><td>KR717101</td><td>QR-CBC51</td><td>140</td><td>320</td><td>320</td><td>200</td><td>170</td><td>130</td></tr><tr><td>(small)</td><td>(9)</td><td>LED dir (Kr91773x)</td><td>140</td><td>300</td><td>300</td><td>157</td><td>170</td><td>140</td></tr><tr><td>(shadow gap - small)</td><td>(2)</td><td>LED dir (Kr91793x)</td><td>140</td><td>344</td><td>344</td><td>120</td><td>390</td><td>115</td></tr><tr><td></td><td>(7)</td><td>LED fixed, WW (Kr91733x, Kr91703x)</td><td>140</td><td>260</td><td>260</td><td>100</td><td>250</td><td>100</td></tr><tr><td></td><td></td><td>Audio</td><td>140</td><td>200</td><td>200</td><td>130</td><td>150</td><td>130</td></tr><tr><td></td><td></td><td>Diapason 40/80/120 base LED</td><td>140</td><td>260</td><td>260</td><td>70**</td><td>110</td><td>70</td></tr><tr><td></td><td></td><td>Holon 80 directional LED</td><td>140</td><td>260</td><td>260</td><td>X**</td><td>110</td><td>60</td></tr><tr><td></td><td></td><td>ATO in-line 80</td><td>140</td><td>300</td><td>300</td><td>157</td><td>170</td><td>140</td></tr><tr><td>Concrete plasterkit aplis IL 120 (shadow gap)</td><td>KR707201</td><td>LED dir., fixed, wallwasher</td><td>140</td><td>350</td><td>350</td><td>150</td><td>305</td><td>200</td></tr><tr><td></td><td>(9)</td><td>LED low</td><td>140</td><td>390</td><td>390</td><td>150</td><td>305</td><td>237</td></tr><tr><td>Concrete plasterkit aplis IL 165 (shadow gap)</td><td>KR717201</td><td>QT12-ax</td><td>200</td><td>200</td><td>450</td><td>200</td><td>210</td><td>195</td></tr><tr><td></td><td>(9)</td><td>QR-LP111</td><td>200</td><td>200</td><td>450</td><td>230</td><td>210</td><td>178</td></tr><tr><td></td><td></td><td>HIT_TC</td><td>200</td><td>200</td><td>450</td><td>230</td><td>210</td><td>225</td></tr><tr><td></td><td></td><td>HIR-CE111</td><td>200</td><td>200</td><td>450</td><td>230</td><td>210</td><td>203</td></tr><tr><td></td><td></td><td>LED dir.</td><td>200</td><td>280</td><td>450</td><td>230</td><td>210</td><td>230</td></tr></tbody></table>	Name	Reference	Lamptype	Ø A	E	F	G	Ø B	D	Concrete plasterkit aplis IL 80 (shadow gap)	KR717101	QR-CBC51	140	320	320	200	170	130	(small)	(9)	LED dir (Kr91773x)	140	300	300	157	170	140	(shadow gap - small)	(2)	LED dir (Kr91793x)	140	344	344	120	390	115		(7)	LED fixed, WW (Kr91733x, Kr91703x)	140	260	260	100	250	100			Audio	140	200	200	130	150	130			Diapason 40/80/120 base LED	140	260	260	70**	110	70			Holon 80 directional LED	140	260	260	X**	110	60			ATO in-line 80	140	300	300	157	170	140	Concrete plasterkit aplis IL 120 (shadow gap)	KR707201	LED dir., fixed, wallwasher	140	350	350	150	305	200		(9)	LED low	140	390	390	150	305	237	Concrete plasterkit aplis IL 165 (shadow gap)	KR717201	QT12-ax	200	200	450	200	210	195		(9)	QR-LP111	200	200	450	230	210	178			HIT_TC	200	200	450	230	210	225			HIR-CE111	200	200	450	230	210	203			LED dir.	200	280	450	230	210	230
Name	Reference	Lamptype	Ø A	E	F	G	Ø B	D																																																																																																																																										
Concrete plasterkit aplis IL 80 (shadow gap)	KR717101	QR-CBC51	140	320	320	200	170	130																																																																																																																																										
(small)	(9)	LED dir (Kr91773x)	140	300	300	157	170	140																																																																																																																																										
(shadow gap - small)	(2)	LED dir (Kr91793x)	140	344	344	120	390	115																																																																																																																																										
	(7)	LED fixed, WW (Kr91733x, Kr91703x)	140	260	260	100	250	100																																																																																																																																										
		Audio	140	200	200	130	150	130																																																																																																																																										
		Diapason 40/80/120 base LED	140	260	260	70**	110	70																																																																																																																																										
		Holon 80 directional LED	140	260	260	X**	110	60																																																																																																																																										
		ATO in-line 80	140	300	300	157	170	140																																																																																																																																										
Concrete plasterkit aplis IL 120 (shadow gap)	KR707201	LED dir., fixed, wallwasher	140	350	350	150	305	200																																																																																																																																										
	(9)	LED low	140	390	390	150	305	237																																																																																																																																										
Concrete plasterkit aplis IL 165 (shadow gap)	KR717201	QT12-ax	200	200	450	200	210	195																																																																																																																																										
	(9)	QR-LP111	200	200	450	230	210	178																																																																																																																																										
		HIT_TC	200	200	450	230	210	225																																																																																																																																										
		HIR-CE111	200	200	450	230	210	203																																																																																																																																										
		LED dir.	200	280	450	230	210	230																																																																																																																																										
1 cut out	<p>** Mind that the driver dimensions WxH cannot exceed 67x29,5mm! the length of the driver determines G as it has to be pushed perpendicular through the plasterkit. Depth = length of the driver + 30mm (in case of Holon 80 when the standard drivers KR77223x G = 130mm)</p> 																																																																																																																																																	
2 dimensions	<p>Aplis in-line 80</p> <p>Aplis in-line 80 (small concr. Plasterkit)</p> <p>Aplis in-line 120</p> <p>Aplis in-line 165</p>																																																																																																																																																	
3 installation	<p>Reinforce perfo plate with gypsum plate or wooden plate to avoid bending.</p>  <p>Put the plasterkit through the hole.</p>  <p>Fix the plasterkit with screws.</p>  <p>In case of 80 range please make sure that sticker is removed before proceeding!</p>	<p>In case of aplis IL 165.</p>  <p>Align the box with the plasterboard using the thumb screw. Fix these screws with a hexagon screw key.</p>  <p>Fill around perimeter of plasterkit using suitable filler and plaster to hide screws and plasterkit.</p> <p>Minimum filler distance, spread out until zero.</p>																																																																																																																																																
4 installation	<p>Industrieweg Noord 1152 3660 Opglabbeek Belgium</p>	<p>Tel + 32 89 81 97 80 Fax + 32 89 81 97 90</p> <p>www.kreon.com mailbox@kreon.be</p> <p>revision date: 24/05 /2018 KR8170001800</p>																																																																																																																																																