










technics		<table><tr><th>Name</th><th>Reference</th><th>Lamptype</th><th>ØA</th><th>BxC</th><th>Dmin</th><th>ExF</th><th>Gmin</th><th>Tmin-Tmax</th></tr><tr><td rowspan="4">Plasterkit aplis in-line 120 (shadow gap)</td><td rowspan="4">KR707204 (8)</td><td>LED dir, fixed, wallwasher</td><td>144</td><td></td><td></td><td>350x350</td><td>150</td><td></td></tr><tr><td>LED dir, fixed, wallwasher</td><td>144</td><td></td><td></td><td>350x350</td><td>150</td><td></td></tr><tr><td>LED dir low</td><td>144</td><td></td><td></td><td>400x400</td><td>140</td><td></td></tr><tr><td>LED dir low</td><td>144</td><td></td><td></td><td>400x400</td><td>140</td><td></td></tr><tr><td colspan="8">Plasterboard thickness 120 range</td><td>9-26</td></tr></table>	Name	Reference	Lamptype	ØA	BxC	Dmin	ExF	Gmin	Tmin-Tmax	Plasterkit aplis in-line 120 (shadow gap)	KR707204 (8)	LED dir, fixed, wallwasher	144			350x350	150		LED dir, fixed, wallwasher	144			350x350	150		LED dir low	144			400x400	140		LED dir low	144			400x400	140		Plasterboard thickness 120 range								9-26
Name	Reference	Lamptype	ØA	BxC	Dmin	ExF	Gmin	Tmin-Tmax																																										
Plasterkit aplis in-line 120 (shadow gap)	KR707204 (8)	LED dir, fixed, wallwasher	144			350x350	150																																											
		LED dir, fixed, wallwasher	144			350x350	150																																											
		LED dir low	144			400x400	140																																											
		LED dir low	144			400x400	140																																											
Plasterboard thickness 120 range								9-26																																										
1 cut out		<table><tr><th>Name</th><th>Reference</th><th>Visible J</th></tr><tr><td>Aplis in-line 120 plasterkit no shadow gap</td><td>KR707204</td><td>Ø 120</td></tr><tr><td>Aplis in-line 120 plasterkit shadow gap</td><td>KR707208</td><td>Ø 126</td></tr></table>	Name	Reference	Visible J	Aplis in-line 120 plasterkit no shadow gap	KR707204	Ø 120	Aplis in-line 120 plasterkit shadow gap	KR707208	Ø 126																																							
Name	Reference	Visible J																																																
Aplis in-line 120 plasterkit no shadow gap	KR707204	Ø 120																																																
Aplis in-line 120 plasterkit shadow gap	KR707208	Ø 126																																																
2 dimensions	<p>Round plasterkit</p>  <div data-bbox="992 932 1238 1027"><p>Please make sure that sticker is removed before proceeding!</p></div>  																																																	
3 installation	<p>Put the plasterkit through the hole.</p>  <p>Fix the plasterkit with the screws.</p>  <p>Assembling torque max 20 CN.m.</p> 																																																	
4 installation	<p>Assembling principle</p>  <p>Fill around perimeter of plasterkit using suitable filler and plaster to hide screws and plasterkit.</p> <p>Minimum filler distance, spread out until zero.</p>																																																	
kreon nv	Industrieweg Noord 1152 3660 Opglabbeek Belgium	Tel + 32 89 81 97 80 Fax + 32 89 81 97 90 www.kreon.com mailbox@kreon.be revision date: 05/01/17 KR8079332126 Sheet 1/1																																																